



# TRANS POLY GEAR MTF 75W80

This is a fully synthetic lubricant based on carefully selected very high quality base oils, which is recommended for the manual transmissions of most commercial vehicles. It is adapted to the requirements of syncromesh transmissions, procuring improved shift comfort, low temperature fluidity and longer service life.

### TRANS POLY GEAR MTF 75W80 meets the following specifications:

- MAN: 341 E-3, 341 Z-4
- MB: 235.4
- VOLVO: 97305, 97307
- ZF: TE-ML 01L, TE-ML 02L, TE-ML 08, TE-ML 16K

#### **APPLICATIONS:**

This product meets the requirements of many commercial vehicle builders and/or gearbox manufacturers, including DAF, IVECO, Eaton Europe (300.000 km or 3 years), Renault (in accordance with B0032/2 Annex 3) and Volvo.

#### TYPICAL CHARACTERISTICS:

Test	Unit	Average Value
Density at 15°C	kg/m3	858
Viscosity 40°C	cSt	580
Viscosity 100°C	cSt	97.5
Viscosity Index		154
Flash Point COC	°C	234
Pour Point	°C	-45
Brookfield viscosity at -40 °C	mPas	80 <mark>000</mark>

#### Packaging available:

1 Liter

## 4 Liters

5 Liters



20 Liters

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.