



KROSS

Empowering Oil



TRANS Matic DEXRON 6

This is a full synthetic lubricant based on carefully selected very high quality base oils, which meets the requirements of the General Motors Dexron VI specification. Its special composition allows it to be used in all applications, where the older Dexron II and Dexron III fluids are recommended.

TRANS Matic DEXRON 6 meets the following specifications:

- Dexron VI
- Mercon LV
- MB 236.1/236.5/236.7/236.8/236.9/236.41
- VAG G-055-025/G-052-162
- Aisin Warner JWS 3309/3324 (WS)
- Allison TES 228/C3/C4
- BMW ETL7045/7045E/8072B/LA2634/Mini Cooper T-IV
- Chrysler Dodge Mopar AS68RC (Type IV), ATF+2/+3/+4, Fiat Typer IV
- Ford Mercon /WSS-M2C138-CJ/166-H/922-A1/924-A
- GM Dexron IID/IIIE/IIIG/IIIH/TASA
- Honda Acura DW-1/ATF-Z1 (except in CVT)
- Hyundai/Kia SP-II/SP-III/SP-IV/SP-IV M/SP-IV RR
- Hyundai/Kia JWS3314/9683
- Isuzi Besco atf ii/iii, Nissan Matic C/D/J/K/S
- Jaguar ATF 3403 M115/JLM 20238
- JASO M315-2013 1A/1A-LV/2A
- Mazda ATF DII/M-III/M-V/FZ/F-1/S-1/N-1/3317
- Mitsubishi SK/SP-II/SP-III/SP-IV/AW/J2/J3/ATF PA
- Opel, Porsche ATF 3403-M115/Type IV
- Subaru ATF/ATF 5AT/ATF HP
- Suzuki ATF3309/3314/3317/2326/2384 K
- Toyota D-II/D-III/T-III/T-IV/WS 1161540/97340
- Voith 55.6335, Volvo 1161540/97340
- ZF 5HP 18FL/19FL/24A/30/4 HP 20, ZF TE-ML 11A/11B

APPLICATIONS:

This high quality ATF can be used in automatic transmissions with torque converters of passenger cars, as well as in wet clutches and power steering units.

TYPICAL CHARACTERISTICS:

Test	Unit	Average Value
Density at 15°C	kg/m ³	847
Viscosity 40°C	cSt	300
Viscosity 100°C	cSt	60
Viscosity Index		151
Brookfield viscosity at -40 °C	mPas	12000
Color		red

Packaging available:



We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.