



KROSS

Empowering Oil



TRANS UNI MATIC ATF

This is a full synthetic lubricant based on carefully selected very highly refined base oils for automatic transmissions, meeting the requirements of most American, Japanese and European manufacturers.

TRANS UNI MATIC ATF meets the following specifications:

- AISIN-WARNER: JWS 3309
- JWS 3314, JWS 3317
- ALLISON : TES 295
- BMW: ETL 7045E, ETL 8072B
LA 2634, LT 71141
- CHRYSLER: ATF +3 AND +4
- FIAT: 9.55550-AV4
- FORD: MERCON V,
WSS-M2C922-A1
- GM: DEXRON III-H, III-G & IID
- HONDA: ATF Z-1
- HYUNDAI: SP-III
- MB: 236.10, 236.11, 236.3
236.5, 236.7
- NISSAN: MATIC-K, MATIC-W
- PSA: P/N Z 000169756
- TOYOTA: TYPE T-IV
- VW: G 052 055, G 052 162,
G 052 533, G 052 990
G 055 025

APPLICATIONS:

Its versatile nature guarantees it can be used in automatic transmissions and torque convertors for most passenger cars, off-road vehicles and SUVs.

TYPICAL CHARACTERISTICS:

Test	Unit	Average Value
Density at 15°C	kg/m ³	849
Viscosity 40°C	cSt	327
Viscosity 100°C	cSt	70,2
Viscosity Index		184
Flash Point COC	°C	218
Pour Point	°C	-48
Brookfield viscosity at -40 °C	mPas	12000
Color		red

Packaging available:



We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.