



KROSS

Empowering Oil



TRANS UNI GEAR S 75W90

This is a full synthetic lubricant based on carefully selected very high quality base oils, which can be used in a wide field of applications. Because of its special composition, it is particularly suited for synchronized gear boxes, as well as heavily loaded differentials.

TRANS UNI GEAR S 75W90 meets the following specifications:

- API: GL-4, GL-5, MT-1
- DAF: GL5/MIL-PRF-2105E
- VECO: VOITH 3.325-340
- MACK: GO-J EO-H
- MAN: 341 E-3, 341 Z-2
342 M-3, 3343 /SL 342 S1/342 SL
- MB: 235.6/235.8
- MIL: PRF-2105E
- RENAULT: B0032/3 Annex 3
- SAE: J 2360
- SCANIA: STO 1
- ZF: TE-ML 02B, TE-ML 05B,
TE-ML 07A, TE-ML 08, TE-ML 12B
TE-ML 12L, TE-ML 12N, TE-ML 16F
TE-ML 17B, TE-ML 19C
TE-ML 21B
- TMS 6816
- DIN 51517

APPLICATIONS:

This oil is recommended for all components of mechanical transmissions (gear boxes, transfer boxes, differentials, etc.). of trucks and four-wheel drive vehicles.

TYPICAL CHARACTERISTICS:

Test	Unit	Average Value
Density at 15°C	kg/m ³	869
Viscosity 40°C	cSt	101
Viscosity 100°C	cSt	154
Viscosity Index		150
Flash Point COC	°C	218
Pour Point	°C	-40
Total Base Number	mgKOH/g	2,1

Packaging available:

1 Liter

4 Liters

5 Liters

✓ 20 Liters

208 Liters

We reserve the right to alter the general characteristics of our products in order to let our customers benefit of the latest technical evolutions.